

***Whatever you're hauling,  
we can take it!***



**AUTO • RACE • CARGO & UTILITY • SNOWMOBILE/SPORT • MOTORCYCLE • GOOSENECK & FIFTH WHEEL**

## **Atlas Specialty Trailers**

21066 Protecta Drive • Elkhart, IN 46516

866-293-6008 • 574-293-6008

[www.AtlasSpecialtyTrailers.com](http://www.AtlasSpecialtyTrailers.com)

# AUTO HAULERS



Atlas auto haulers are known for solid construction. These rounded top trailers are framed with steel tubing with 3/8" plywood lining. Other features are:

- **Frame:** Steel tube main rails, 16" on center chassis, 102" wide, triple tube tongue (20' or longer), beavertail, undercoated chassis, partial side and front posts, dust barrier/sealed sidewalls, welded safety chains w/clasps, formed steel rear header, vertical hat post front wall w/roof bow top & bottom plates, sand pad.
- **Axle & Tire:** Torflex® axle, electric brakes w/breakaway box, E-Z Lube® hubs with grease caps, 15" white spoke wheels, premium radial tires, chromed steel center caps.
- **Exterior:** Seamless one-piece aluminum roofing, .080 mill finish extruded aluminum roof cove, 24" high aluminum tread plate stonguard finished w/ trimlock, .030 smooth aluminum exterior available in a wide range of colors, .030 wrapped rear w/aluminum trim, color matching screws in white, black, red, gray & silver, 5" screw pattern, fiberglass radius front cap, aluminum fenders and skirts, DOT/CSA lighting, sealed clearance lights, rear tail lights mounted in cornerposts, injection molded license plate bracket w/light, 35" vapor barrier.
- **Interior:** 3/4" Advantech decking, 3/8" plywood wall liner, 4-5000# floor D-Rings, 4-12V dome lights, 2-nonpowered roof vents, 2-12V wall switches.
- **Doors:** Welded aluminum frame, tube steel frame side door rough openings, aluminum trimmed rough openings, double sealed 48" side door, 4000# rear ramp spring assist, camlock latches, holdbacks on all doors when applicable, safety spring chains for side door.

Colors in photographs may show options available at additional cost.

# RACE TRAILERS



- **Frame:** Steel tube main rails, chassis cross members 16" on center, 102" wide, triple tube tongue (20' or longer), beavertail, undercoated chassis, partial side posts, partial front posts, dust barrier/sealed sidewalls, welded safety chains w/clasps, formed steel rear header, vertical hat post frame on 16" vertical centers, vertical hat post, front wall with roof bow top & bottom plates, sand pad.
- **Axle & Tire:** Torflex® axle, electric brakes w/breakaway box, E-Z Lube® hubs with grease caps, 15" white spoke wheels, premium radial tires, chromed steel center caps.
- **Exterior:** Seamless one-piece flat top aluminum roofing, .080 mill finish extruded aluminum roof cove, 24" high aluminum tread plate stoneguard finished with trimlock, .030 smooth aluminum exterior available in a wide range of colors, .030 wrapped rear with aluminum trim, color matching screws in white, black, red, gray & silver, 5" screw pattern, fiberglass radius front cap, aluminum fenders and skirts, DOT/CSA lighting, sealed clearance lights, rear tail lights mounted in cornerposts, injection molded license plate bracket w/light, anodized aluminum bright vertical front corners, cast aluminum rear corners & polished aluminum wrapped rear end, 35" vapor barrier, bull nose front top cap.
- **Interior:** White vinyl walls, insulated white vinyl ceiling, 3/4" Advantech decking, 3/8" plywood wall liner, 4 - 5000# D-Rings, 4-12V deluxe dome lights, 2-nonpowered roof vents, 2-12V wall switches.
- **Doors:** Welded aluminum frame, tube steel frame side door rough openings, aluminum trimmed rough openings, double sealed 48" side door, 4000# rear ramp spring assist, camlock latches, holdbacks on all doors when applicable, safety spring chains for side door.

Torflex® and E-Z Lube® are registered trademarks of Dexter Axle, A Tomkins Company.

# CARGO & UTILITY TRAILERS



Atlas utility and cargo trailers begin with the same sturdy undercoated chassis and frame. Utility trailers have spring axles and bias tires, while the cargo trailers feature torsion axles and steel-belted radial tires. Of course, all trailers can be customized to fit your needs.

- **Frame:** Steel tube main rails, triple tube tongue (20' or longer), 24" on center chassis, formed steel rear header, undercoated chassis, dust barrier/sealed sidewalls, safety chains welded.
- **Axle & Tire:**  
*Utility* - Spring Idler Axle w/4" drop, (electric brakes included on 7' wide & larger, 15" white Mod wheels), 15" bias tires  
*Cargo* - Torflex® axle, 15" white D-window wheels, E-Z Lube® hubs w/ grease caps, premium radial tires, chromed steel center cap.
- **Exterior:**  
*Utility* - .030 smooth aluminum exterior, seamless aluminum roofing, .080 mill finished extruded aluminum top wrap, .030 wrapped rear end, DOT/CSA lighting fiberglass radius front caps, aluminum fenders, sealed clearance lights, rear taillights mounted in corner post, injection molded license plate bracket w/ light, 35" vapor barrier wrap.  
*Cargo* - 24" Aluminum tread plate stonequard, .030 smooth aluminum exterior, seamless aluminum roofing, .080 mill finished extruded aluminum top wrap, .030 wrapped rear end, DOT/CSA lighting fiberglass radius front caps, aluminum fenders, sealed clearance lights, rear taillights mounted in corner post, injection molded license plate bracket w/ light, 35" vapor barrier wrap.
- **Interior:** 3/4" Advantech decking, 3/8" plywood liner.
- **Doors:** Aluminum door frames, double rear doors, dual sealed side doors (optional), camlock and barlock door latches, holdbacks on all doors when applicable, safety spring chains on all doors.

Trailers in photographs may show options available at additional cost.

# MOTORCYCLE TRAILERS



Most Atlas motorcycle trailers feature 2-way side vents, a wedge nose, ramp door and side door.

- **Axle & Tire:** Torflex® axle, 15" white D-window wheels, E-Z Lube® hubs w/ grease caps, premium radial tires, chromed steel center caps.
- **Exterior:** 24" aluminum tread plate stoneguard, .030 smooth aluminum exterior available in a wide range of colors, seamless aluminum roofing, custom graphics, anodized trimmed rear hoop, aluminum tread plate trimmed front wedge nose, DOT/CSA lighting, fiberglass radius front cap, aluminum fenders, sealed clearance lights, rear tail lights mounted in cornerposts, injection molded license plate bracket w/light, 35" vapor barrier wrap.
- **Interior:** 3/4" Advantech decking, 3/8" plywood wall liner, 2-12V dome lights, 1-wall switch, 6 - 5000# D-Rings, 2-removable wheel chocks, nonpowered roof vent, 2-sidewall vents.
- **Doors:** Aluminum door frames, rear ramp door w/spring assist & barlock door latches, curbside door w/barlock door latches, holdbacks and safety springs on all doors.



# GOOSENECKS & 5TH WHEELS



- **Frame:** Steel tube main rails, 16" on center chassis, formed steel rear header, undercoated chassis, dust barrier/sealed sidewalls, safety chains welded, 8' upper deck included in length measurement. Wedge nose upper deck available for short bed trucks.
- **Axle & Tire:** Torflex® axle, E-Z Lube® hubs w/grease caps, premium radial tires, chromed steel center caps, electric brakes w/breakaway box.
- **Exterior:** 24" Aluminum tread plate stoneguard, .030 smooth aluminum exterior, seamless aluminum roofing, aluminum fenders, DOT/CSA lighting fiberglass radius front cap, sealed clearance lights, rear taillights mounted in corner post, injection molded license plate bracket w/light, 35" vapor barrier wrap. Available options include aluminum treadplate steps, aluminum tread-plate across the front of gooseneck which includes storage door & floor.
- **Interior:** 3/4" Advantech decking, 3/8" plywood liner.
- **Doors:** Aluminum door frames, curbside door w/barlock door latches, holdbacks & safety springs on all doors.

Trailers in photographs may show options available at additional cost.

# SNOWMOBILE/SPORTS TRAILERS



- **Frame:** Steel tube main rails, 24" on center chassis, formed steel rear header, undercoated chassis, dust barrier/sealed sidewalls, safety chains welded, sand pad, 2-sway bar brackets, fuel door.
- **Axle & Tire:** Torflex® axle, E-Z Lube® hubs w/grease caps, premium radial tires, chromed steel center caps, electric brakes w/breakaway box.
- **Front Side Ramp Door:** .030 smooth aluminum exterior, seamless aluminum roofing, non-powered roof vent, aluminum tread plate trimmed v-nose, DOT/CSA lighting fiberglass radius front cap, aluminum fenders, sealed clearance lights, rear taillights mounted in center post, injection molded license plate bracket w/light, 35" vapor barrier wrap.
- **Interior:** 3/4" Advantech decking, 3/8" plywood liner, white vinyl ceiling & sidewall liner w/2' plywood kick plate, helmet cabinet, 2-12V dome lights, 1-wall switch, 5 to 9 1200# D-Rings, depending on model.
- **Doors:** Aluminum door frames, rear ramp door w/spring assist & barlock door latches, curbside door w/barlock door latches, steel ski guard, hold-backs & safety springs on all doors.



# SPECIFICATIONS

	Cargo / Utility A*820TA2	Cargo / Utility A*714TA2	Cargo / Utility A*612SA	Cargo / Utility A*58SA	Autohauler AA8524TA3	Race AR8520TA2	Race AR8524TA3	Race AR8528TA3
Over-all Length	24'	18'	16'	12'	28'	24'	28'	32'
Over-all Width	8'5"	8'1"	7'9"	6'8"	8'6"	8'6"	8'6"	8'6"
Over-all Height (inc. roof vent)	8'10"	8'4"	8'1"	7'0"	8'6"	8'9"	8'9"	8'9"
Platform Height	20"	19"	18"	18"	20"	18"	19"	19"
Interior Height	6'8"	6'1"	6'1"	5'1"	6'8"	7'	7'	7'
Interior Overall Length	20'5"	14'5"	12'4"	8'4"	24'5"	19' 8"	23' 8"	27' 8"
Interior Width	7'8"	6'8"	5'8"	4'8"	8'1"	8'	8'	8'
Between Wheel Wells	6'9"	6'8"	NA	NA	6'9 1/2"	6'9"	6'9"	6'9"
Side Door	Optional	Optional	Optional	Optional	Standard	Standard	Standard	Standard
Side Door Width	32, 36, 48	32, 36	32, 36	24	48"	48"	48"	48"
Side Door Opening Height	5'11"	5'5"	5'3"	4'3"	72"	78 1/2"	78 1/2"	78 1/2"
Rear Door	Double	Double	Double	Double	Ramp	Ramp	Ramp	Ramp
Rear Door Opening Height	5'11 1/2"	5'5 1/2"	5'5 1/2"	4'5 1/2"	75"	83"	83"	85"
Rear Door Opening Width	7'1"	6'	4'11"	4'	89 1/4"	89 1/4"	89 1/4"	89 1/4"
Hitch Weight	300 lbs.	250 lbs.	165 lbs.	100 lbs.	420 lbs.	355 lbs.	420 lbs.	465 lbs.
Ball Size	2-5/16"	2-5/16"	2"	2"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
G.A.W.R.	7,000 lbs.	7,000 lbs.	3,500 lbs.	3,500 lbs.	10,400 lbs.	7,000 lbs.	10,400 lbs.	10,400 lbs.
G.V.W.R.	7,000 lbs.	7,000 lbs.	2,990 lbs.	2,990 lbs.	10,160 lbs.	7,000 lbs.	10,160 lbs.	10,160 lbs.
Curb Weight	2,850 lbs.	2,250 lbs.	1,390 lbs.	1,010 lbs.	4,200 lbs.	3,550 lbs.	4,200 lbs.	4,650 lbs.
Payload Capacity	4,150 lbs.	4,750 lbs.	1,600 lbs.	1,980 lbs.	5,960 lbs.	3,450 lbs.	5,960 lbs.	5,510 lbs.
Brakes	Electric	Electric	Optional	Optional	Electric	Electric	Electric	Electric
Tires	ST205/75R15	ST205/75R15	ST205/75R15	ST205/R15	ST225-75R15	ST205-75R15	ST225-75R15	ST225-75R15
Wheels	5 Bolt	5 Bolt	5 Bolt	5 Bolt	6 Bolt	5 Bolt	6 Bolt	6 Bolt
Frame	6" Tube	6" Tube	3" Tube	3" Tube	6" Tube	6" Tube	6" Tube	8" Tube
Floor	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Floor Crossmember Loc.	24" O/C	24" O/C	24" O/C	24" O/C	16" O/C	16" O/C	16" O/C	16" O/C
Wall Covering	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	White Vinyl	White Vinyl	White Vinyl
Wall Post Loc.	16" O/C	16" O/C	16" O/C	16" O/C	16" O/C	16" O/C	16" O/C	16" O/C
Roof 24" O/C								

Model number of any particular unit does not necessarily reflect the overall length of the unit. All illustrations and Specifications contained in this literature are based on the latest product information at time of publication.



Portions of this catalog were used with the expressed authority of Dexter Axle, but Dexter Axle is not responsible for the accuracy of the information contained therein.



## BUILT FOR STRENGTH, BUILT TO LAST

Atlas Specialty Trailers is a manufacturer of quality-built enclosed cargo trailers. Widths of 4', 5', 6', 7', 8', and 8.5' and lengths from 6' thru 40' are available. A wide variety of options are available, and every trailer comes with a full three (3) year limited structural warranty. All trailers are enclosed and manufactured in Elkhart, Indiana, using steel frame construction,

3/8" plywood-lined interiors and colored aluminum exterior.

Atlas Specialty Trailers are competitively priced within the industry, and the fit & finish of each trailer is **"THE FINEST THERE IS!"**



**AUTO • RACE • CARGO & UTILITY • SNOWMOBILE/SPORT • MOTORCYCLE • GOOSENECK & FIFTH WHEEL**

Your Atlas Dealer is: